

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
23 June 2005 (23.06.2005)

PCT

(10) International Publication Number
WO 2005/057903 A2

(51) International Patent Classification⁷: **H04N**

Vladimir [IL/IL]; 9 Kinor St., 75575 Rishon Lezion (IL).

(21) International Application Number:
PCT/IL2004/001055

BARON, Natan [IL/IL]; 22 Haoren St., 44813 Oranit (IL).

(22) International Filing Date:
17 November 2004 (17.11.2004)

(74) Agent: **RECHES, Oren**; 13 Hadafna St., POB 913, 42823 Zoran (IL).

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/528,510 11 December 2003 (11.12.2003) US
60/538,517 11 December 2003 (11.12.2003) US

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(71) Applicant (for all designated States except US): **AD-
VASENSE TECHNOLOGICS (2004) LTD.** [IL/IL]; 11
Hamenofim St., POB 2148, 46120 Herzeliya (IL).


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

(72) Inventors; and

(75) Inventors/Applicants (for US only): **KOIFMAN,**

[Continued on next page]

(54) Title: APPARATUS AND A METHOD FOR LOW NOISE SENSING



(57) Abstract: The invention provides a method and apparatus. The apparatus includes a pixel adapted to receive light and to output a current representative of the received light; a feedback circuitry, connected to the pixel, adapted to receive said current and to receive a reference current and to provide a feedback signal to the pixel at least during at least a reset stage of the pixel. The method includes: (i) receiving light, by a pixel, and providing a pixel output signal representative of the received light; (ii) receiving, by a feedback circuitry, the pixel output signal; and (iii) providing multiple feedback signals to the pixel at least during a reset stage of the pixel.

WO 2005/057903 A2



ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *without international search report and to be republished upon receipt of that report*